



**TYPE APPROVAL CERTIFICATE**  
No. **ELE058611XT/001**

**This is to certify** that the product below is found to be in compliance with the applicable requirement of the RINA type approval system.

<i>Description</i>	<b>ELECTRIC CABLES</b>
<i>Type</i>	<b>FM2XACY 150/250 V</b>
<i>Applicant</i>	<b>2M KABLO SANAYI VE TICARET A.S. SANCAKTEPE MAHALLESİ, KLAS SOKAK, NO:8, 34580 SILIVRI, ISTANBUL, TURKEY</b>
<i>Manufacturer</i>	<b>2M KABLO SANAYI VE TICARET A.S.</b>
<i>Place of manufacture</i>	<b>SANCAKTEPE MAHALLESİ, KLAS SOKAK, NO:8, 34580 SILIVRI, ISTANBUL, TURKEY</b>
<i>Reference standards</i>	<b>IEC 60092-350; IEC 60092-376.</b>

*Issued in* **ISTANBUL** on **August 16, 2013**. *This Certificate is valid until* **August 16, 2018**



RINA  
**Orhan Pekcay**

This certificate consists of this page and 1 enclosure



**TYPE APPROVAL CERTIFICATE**

No. **ELE058611XT/001**

**Enclosure - Page 1 of 1**

**FM2XACY 150/250 V**

**Materials/Components**

Shipboard instrumentation, control and communication cables, flame retardant, for ships and off-shore units installation.

Rated voltage: 150 / 250 V

Maximum rated conductor temperature: + 85 °C

Type: FM2XACY

Marking: 2MKABLO IEC 60092-376 FM2XACY n x m x s(mm2) 150/250 V IEC 60332-3-22 [METER MARK]

**Construction**

Conductor: Stranded Electrolytic Annealed Copper Class 2

Insulation: XLPE

Individual Shielding: AL-PES foil (with stranded tinned copper drain wire)

Lay-Up: Shielded pairs and quads are stranded in layers

Screen: Electrolytic Copper Wire Braiding

Outer Sheath: PVC (ST2)

Number of Units: 1, 2, 4, Cross-sectional area of conductors 0,5 and 0,75 mm<sup>2</sup>

Number of Units: 7, 10,14, 19, 24 Cross-sectional area of conductors 0,75 mm<sup>2</sup>

**Reference documents :** Technical Specification No: 106-3/2011 (15/03/2012)

**Reference Standards:** IEC 60092-350; IEC 60092-376; IEC 60332-3-22; IEC 60332-1-2; IEC 60228; IEC 60811; IEC 60754-1; IEC 60754-2; IEC 60092-351; IEC 60092-359

**ISTANBUL August 16, 2013**

